

KOHLER®

Roughing-In

K-1139-CN

PROFLEX® 6036

ACRYLIC CUSTOM BATH WHIRLPOOL

Product Information

Applicable product:				
Bath whirlpool, drop-in, custom pump		K-1139-CN		
Recommended accessories:				
Cable drain with PVC tubing		K-7213		
Cable drain without PVC tubing		K-7214		
Trip lever drain		K-11677		
Fixture*:				
Bathing well:				
Basin area	46" (116.8 cm) x 15" (38.1 cm)			
Top area	55" (139.7 cm) x 25" (63.5 cm)			
To overflow:				
Water depth	14" (35.6 cm)			
Capacity	57 gal (215.8 L)			
Weight	55 lbs (24.9 kg)			
Drop-in cutout	58-1/2" (148.6 cm) x 34-1/4" (87.6 cm)			
* Approximate measurements for comparison only.				
Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (181 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

No change in measurements if connected with drain illustrated. (K-11677)

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

