

# KOHLER® Roughing-In

## K-1146-HK, K-1146-HN PROFLEX® 6040 CUSTOM BATH WHIRLPOOL WITH HEATER

### Product Information

Applicable products:	
Custom bath whirlpool with heater – drop-in	K-1146-HK
Custom bath whirlpool with heater – drop-in	K-1146-HN

Fixture*:	
Bathing well:	
Basin area, bottom	46" (116.8 cm) x 19" (48.3 cm)
Basin area, top	55" (139.7 cm) x 29" (73.7 cm)
Weight	61 lbs (27.7 kg)
To overflow:	
Water depth	14" (35.6 cm)
Capacity	54 gal (204.4 L)
* Approximate measurements for comparison only.	

Pump:	V	Hz	A	
1-speed	120	60	7.5	
Heater:	KW	V	Hz	A
	1.5	120	60	12.5
* Approximate measurement for comparison only.				

Included components:	
Cut-out template	114859-7

### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 32 lbs/square foot (157.2 kg/square meter) loading.

**NOTICE:** The pump must be relocated to its custom position at the time of installation. Provide adequate clearance between the floor and the pump.

The suction line extends 1" (2.5 cm) beyond the edge of the rim. The pump base extends 1-1/8" (2.9 cm) beyond the edge of the rim. Modify the framing as needed.

A minimum access panel is required at the pump location, as illustrated. The access panel should be 20" (50.8 cm) wide and 15" (38.1 cm) high.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with the drain illustrated. (K-11677 or K-11677M)

