

ProFlex® 7242

6' Whirlpool Bath K-1148



Features

- Center drain.
- Integral lumbar support and armrests for comfort.
- 72" (1829 mm) x 42-1/8" (1070 mm) x 19-3/4" (502 mm)

Material

Acrylic

Hydrotherapy

- Single-speed whirlpool offers six fully adjustable hydro-massage jets for water flow and direction.
- Pump with air switch for whirlpool.

Installation

Drop-in

Recommended Accessories

K-7213 27" Cable Bath Drain K-7214 27" Cable Bath Drain K-11677 Bath Drain K-24916 Wireless Music Kit K-1491 Bath/Whirlpool Pillow K-1601 Bath/Whirlpool Footstop K-7259 Clearflo Bath Drain K-9696 Whirlpool 6-Jet Trim Kit



Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 UL 1795 Greenguard UL 2818 - Gold CARB P2

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	96	Biscuit
	47	Almond







ProFlex® 7242

6' Whirlpool Bath K-1148







Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Pump: 120 V, 15 A, 60 Hz

Technical Information

All product dimensions are nominal.

Installation: Drop-in Drain location: Center

Basin area, bottom: 53" x 26" (1346 mm x 660 mm) Basin area, top: 65" x 34" (1651 mm x 864 mm)

Weight: 74 lbs (33.6 kg)

Minimum floor load: 36 lbs/ft² (175.8 kg/m²)

Water depth: 15" (381 mm)
Water capacity: 78 gal (295.3 L)

Template: Drop-in, 114861-7, required, included

Electrical component Pump: 120 V, 7.5 A, 60 Hz

rating:

Pump speed: Single

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Provide one grounded electrical outlet within 24" (610 mm) of each component.

