

Product Information

Applicable products:				
Bubblemassage bath – less chromatherapy	K-1418-G			
Bubblemassage bath – with chromatherapy	K-1418-GCR			
Fixture*:				
Basin area:				
Bathing well	48" (121.9 cm) x 27" (68.6 cm)			
Top area	60" (152.4 cm) x 30" (76.2 cm)			
Weight	150 lbs (68 kg)			
To overflow:				
Water depth	16" (40.6 cm)			
Capacity	94 gal (355.8 L)			
* Approximate measurements for comparison only.				
Drop-in cut-out		70-1/2" (179.1 cm) x 40-1/2" (102.9 cm)		
Blower motor:	Heater	V	Hz	A
	300 W	220-240	50/60	3

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Blower motor:	220-240 V, 15 A, 50/60 Hz

Installation Notes

NOTICE: If the blower motor and check valve are relocated, the following two procedures are required: 1. Provide two access panels. Locate one access panel at the blower motor/control location and the other access panel at the control box. **2.** Relocate the blower motor and the check valve together. Do not relocate one without the other.

Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 54 lbs/square foot (261 kg/square meter) loading.

A blower motor access panel is required.

If used, the optional apron must be installed before the finished floor and wall materials are installed.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to tolerances in ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain shown. (K-7161-AF or K-7161M-AF)

