

Product Information

Applicable product:	
Bath whirlpool module left drain – integral flange	K-1683-H
Bath whirlpool module right drain – integral flange	K-1684-H

Fixture*:	
Basin area:	
Bathing well	46" (116.8 cm) x 23" (58.4 cm)
Top area	54" (137.2 cm) x 27" (68.6 cm)
Weight	205 lbs (93 kg)
To overflow:	
Water depth	11-7/8" (30.2 cm)
Capacity	55 gal (208.2 L)
* Approximate measurements for comparison only.	

Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater:	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 48 lbs/square foot (232 kg/square meter) loading.

Shimming is required to level the fixture.

Stud opening tolerance is (+ 1/4" (6 mm) - 0" (0 mm)). When fire rated wall is specified, dimensions are to the inside of the wall board. Some shimming between stud frame and fixture may be required.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

