

Product Information

| Applicable product: | |
|---|-----------|
| Class Five toilet – left-hand trip lever | K-3947 |
| Class Five toilet – right-hand trip lever | K-3947-RA |
| Class Five toilet – right-hand trip lever with tank locks and Insuliner | K-3947-RZ |
| Class Five toilet – left-hand trip lever with tank locks | K-3947-T |
| Class Five toilet – right-hand trip lever with tank locks | K-3947-TR |
| Class Five toilet – left-hand trip lever with Insuliner | K-3947-U |
| Class Five toilet – right-hand trip lever with Insuliner | K-3947-UR |
| Class Five toilet – left-hand trip lever with tank locks and Insuliner | K-3947-UT |
| | |

| Fixture: | |
|------------------------|---|
| Configuration | two-piece, round |
| Water per flush | 1.28 gpf (4.8 lpf) |
| Passageway | 2-1/8" (5.4 cm) |
| Water area | 10-1/2" (26.7 cm) x 7-3/4" (19.7 cm) |
| Water depth from rim | 5-1/4" (13.3 cm) |
| Seat post hole centers | 5-1/2" (14 cm) |

| Included components: | |
|-------------------------|---------|
| Bowl | K-4197 |
| Tank | K-4841 |
| Tank cover | 1145223 |
| Trip lever | K-9379 |
| Tank attachment kit | 1016548 |
| Bolt cap accessory pack | 1013092 |

Installation Notes

Install this product according to the installation guide.

Fixture conforms to ASME standard A112.19.2/CSA B45.1. All dimensions are nominal.

