

Product Information

Applicable product:	
Class Five toilet – left-hand trip lever	K-3948
Class Five toilet – right-hand trip lever	K-3948-RA
Class Five toilet – right-hand trip lever with tank locks and Insuliner®	K-3948-RZ
Class Five toilet – left-hand trip lever with tank locks	K-3948-T
Class Five toilet – right-hand trip lever with tank locks	K-3948-TR
Class Five toilet – left-hand trip lever with Insuliner	K-3948-U
Class Five toilet – right-hand trip lever with Insuliner	K-3948-UR
Class Five toilet – left-hand trip lever with tank locks and Insuliner	K-3948-UT

Fixture:	
Configuration	two-piece, elongated
Water per flush	1.28 gpf (4.8 lpf)
Passageway	2-1/8" (5.4 cm)
Water area	11-1/4" (28.6 cm) x 8-1/4" (21 cm)
Water depth from rim	5-1/4" (13.3 cm)
Seat post hole centers	5-1/2" (14 cm)

Included components:	
Bowl	K-4198
Tank	K-4841
Tank cover	1145223
Trip lever	K-9379
Tank accessory pack	1016548
Bolt cap accessory pack	1013092

Installation Notes

Install this product according to the installation guide.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

