

Barrington™ Pressure Lite® Toilet K-3554-RA

Features

- Vitreous china.
- Elongated bowl
- Equipped with Sloan FLUSHMATE®— Sloan® Valve Company.
- Polished chrome trip lever.
- Rear outlet.
- 12" (305 mm) x 10" (254 mm) water area.
- 4" (102 mm) rough-in.
- Less seat and supply.
- 1.6 gpf (6.0 lpf).
- 31-1/2" (800 mm) x 21-1/4" (540 mm) x 29-1/4" (743 mm).

Optional Accessories

K-4650 Toilet Seat

K-4652 Toilet Seat

K-7637 Angle Supply with Stop (single)

K-4652-A Toilet Seat

K-4679-CA Commercial Toilet Seat

K-9481-L Left-hand Trip Lever

Components

Product includes:

K-4327 Toilet Bowl

K-4645-RA Toilet Tank

Additional included component/s: Tank cover, Trip lever, Floor screws and bolt caps, Bolt cap accessory pack, Tank accessory pack, and Equipped with Sloan FLUSHMATE® – Sloan® Valve Company.



Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	7	Black Black™





Barrington™

Pressure Lite® Toilet
K-3554-RA



Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Wall

Bowl shape: Elongated front
Flush type: Pressure Assisted
Trap passageway: 2-1/4" (57 mm)

Water surface size: 12" x 10" (305 mm x 254 mm)

Rim to water surface: 7" (178 mm)
Rough-in: 4" (102 mm)
Seat-mounting holes: 5-1/2" (140 mm)

Fixture Supply Requirements

Min static pressure: 20 psi (137.9 kPa) Max static pressure: 80 psi (551.6 kPa)

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

