

Highline® Class Five® Toilet K-3713-BA

Features

- Vitreous china.
- Two-piece toilet.
- Comfort Height® Elongated bowl.
- Class Five® flushing system.
- Includes right-hand polished chrome trip lever.
- 1.28 gpf (4.8 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 10" (254 mm) rough-in.
- Less seat and supply.
- 11-3/8" (289 mm) x 8" (203 mm) water area.
- 29-1/2" (749 mm) x 19-5/8" (498 mm) x 30-3/8" (772 mm).
- Floor mount / Floor Outlet.



K-1954 Touchless Toilet Flush Kit

K-4008 Toilet Seat

K-4108 Toilet Seat with Cleansing Functionality

K-4636 Toilet Seat

K-4652 Toilet Seat

K-4659 Toilet Seat

K-4684 Toilet Seat

K-4688 Toilet Seat

K-4694 Toilet Seat

K-4709 Toilet Seat with Cleansing Functionality

K-4713 Toilet Seat

K-4732 Toilet Seat

K-4733 Toilet Seat

K-4737 Toilet Seat with Cleansing Functionality

K-4748 Toilet Seat

K-4774 Toilet Seat

K-4814 Toilet Seat

K-4888 Elongated Toilet Seat

K-5588 Elongated Toilet Seat

K-5638 Elongated Toilet Seat

K-7637 Angle Supply with Stop (single)

K-4712-T Toilet Seat

K-4731-C Commercial Heavy-duty Toilet Seat

K-4761-BN Toilet Seat

K-4761-CP Toilet Seat

K-9380-R Right-hand trip lever

Components

Product includes:

K-4373 Toilet Bowl

K-4436-RA Toilet Tank

Additional included component/s: Tank cover, Trip lever, Bolt

cap accessory pack, and Tank accessory pack.





ADA CSA B651

51 || OBC

Codes/Standards

ASME A112.19.2/CSA B45.1

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.


| Color | Code | Description |
|-------|------|-------------|
| | 0 | White |
| | 96 | Biscuit |
| | 47 | Almond |





Highline®

Class Five® Toilet K-3713-RA



Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Floor

Bowl shape: Elongated front Flush type: Class Five Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.28 gpf (4.8 lpf)

Water surface size: 11-3/8" x 8" (289 mm x 203 mm)

Rim to water surface: 5-7/8" (149 mm)
Rough-in: 10" (254 mm)
Seat-mounting holes: 5-1/2" (140 mm)

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing Codes require elongated toilets and elongated, open-front toilet seats in public bathrooms.

Accessibility standards require controls to be located on the open side of the toilet.

