

Product Information

Applicable product:		
Comfort Height toilet – Cla left-hand trip lever	assic design,	K-3812
Comfort Height toilet – Claright-hand trip lever	assic design,	K-3812-RA
Comfort Height toilet – Sta left-hand trip lever	ately design,	K-3813
Comfort Height toilet – Staright-hand trip lever	ately design,	K-3813-RA
ADA compliant when installation notes.	lled following	ADA

Fixture:	
Configuration	one-piece, elongated
Water per flush	1.28 gal (4.8 L)
Passageway	2-1/8" (5.4 cm)
Water area	11" (27.9 cm) x 8-3/4" (22.2 cm)
Water depth from rim	6" (15.2 cm)
Seat post hole centers	5-1/2" (14 cm)

Included components:		
Tank cover – Classic design OR	88871	
Tank cover – Stately design	88872	
Trip lever – left-hand OR	K-9167-L	
Trip lever - right-hand	K-9167-R	
Toilet seat	K-4733	
Tank accessory pack	52265	
Bolt cap accessory pack	52048	

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

