

## K-6585 IRON/TONES™ TOP-MOUNT OR UNDER-MOUNT KITCHEN SINK

## **Product Information**

Applicable product:		
Kitchen sink		K-6585
Fixture*:		
Bowl area	21" (533 mm) x 16" (406 mm)	
Water depth	7-1/2" (191 mm)	
Drain hole	Ø 3-7/8" (98 mm)	
* Approximate measu	rements for comparisor	n only.
Optional accessories: Bottom bowl rack		
<b>'</b>		K-3192
<b>'</b>		K-3192 K-3277
Bottom bowl rack		
Bottom bowl rack Wire rinse basket	ard	K-3277
Bottom bowl rack Wire rinse basket Hardwood cutting boa	ard ainer	K-3277 K-3294
Bottom bowl rack Wire rinse basket Hardwood cutting boa Duostrainer® sink stra	ard ainer :	K-3277 K-3294

## **Installation Notes**

Install this product according to the installation guide.

Supplied bowl clamp assemblies require 1" (25 mm) minimum countertop thickness. Installer must supply hardware for thinner countertops.

For multiple bowl under-mount installations, a minimum distance of 3-3/8" (86 mm) is required between bowls. Countertop supplier to determine required support.

Fixture conforms to ASME standard A112.19.1/CSA B45.2. All dimensions are nominal.



