

KOHLER® Roughing-In

**K-865-H2, K-865-N1
TEA-FOR-TWO®
6' BATH WHIRLPOOL**

Product Information

Applicable products:	
6' bath whirlpool	K-865-N1
6' bath whirlpool with neckjets and pillow	K-865-H2

Fixture*:	
Bathing well:	
Basin area, bottom	49" (124.5 cm) x 22" (55.9 cm)
Basin area, top	62" (157.5 cm) x 28" (71.1 cm)
Weight	455 lbs (206.4 kg)
To overflow:	
Water depth	17" (43.2 cm)
Capacity	89 gal (336.9 L)
* Approximate measurements for comparison only.	

Product	kW	V	A*
Neckjets	1.5	240	15
Without neckjets	1.5	240	11
* Approximate measurements for comparison only.			

Drop-in cut-out	70-1/4" (178.4 cm) x 34-1/2" (87.6 cm)
Cut-out for undermount	K-582 template for K-865-H2 only

Required accessories:	
Jet trim kit	K-9696

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 69 lbs/square foot (333 kg/square meter) loading.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Hot water supply should be 70% of capacity or greater. Installations will vary.

K-865-N1 cannot be undermounted.

Fixture conforms to ASME Standard A112.19.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7169-AF or K-7169M-AF)

