

### Product Information

Applicable product:	
Shower trim with plain cross handles	K-T13134-3A
Valve trim with plain cross handles	K-T13135-3A
Shower trim with grooved cross handles	K-T13134-3B
Valve trim with grooved cross handles	KT-13135-3B
Shower trim with plain lever handles	K-T13134-4A
Valve trim with plain lever handles	K-T13135-4A
Shower trim with grooved lever handles	K-T13134-4B
Valve trim with grooved lever handles	KT-13135-4B
Handles are ADA compliant when installed per the requirements of the Accessibility Guidelines. <b>ADA</b>	
Requires a Rite-Temp® K-304-K, K-304-KS, or HiFlow Rite-Temp K-306-KS pressure-balancing valve.	
Optional accessories:	
Deep rough-in kit	73418

### Installation Notes



**CAUTION: Risk of damage to the K-306-KS valve assembly.** When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

