

Features

- End drain.
- Slotted overflow for deep soaking.
- Integral grip rail along sides of bath.
- Integral lumbar support.
- 65-7/8" (1673 mm) x 32-5/16" (821 mm) x 18" (457 mm)

Material

- Cast iron with Safeguard® finish.

Installation

- Drop-in

Required Accessories

K-7271 Brass Slotted Overflow Bath Drain
or
K-7272 PVC Slotted Overflow Bath Drain

Recommended Accessories

K-1172 Adjustable Feet
K-1844 Wood Bath Seat
K-952 Wall-mount Non-diverter Bath Spout
K-1491 Bath/Whirlpool Pillow
K-1601 Bath/Whirlpool Footstop
8360
K-T10059-9
K-T14428-3
K-T14428-4
K-T16237-3
K-T16237-4



ADA

Codes/Standards



ASME A112.19.1/CSA B45.2
ASTM F462
ADA
ICC/ANSI A117.1


KOHLER® Lifetime Limited Warranty for Cast Iron Components

See website for detailed warranty information.



Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit



No change in measurements if connected with drain illustrated. (K-7271 or K-7272)



Technical Information

All product dimensions are nominal.

Installation:	Drop-in
Drain location:	End
Basin area, bottom:	45-3/4" x 21-3/8" (1162 mm x 543 mm)
Basin area, top:	53-7/8" x 25-1/8" (1368 mm x 638 mm)
Weight:	360 lbs (163.3 kg)
Minimum floor load:	61 lbs/ft² (297.8 kg/m²)
Water depth:	13-7/8" (352 mm)
Water capacity:	61 gal (230.9 L)
Cutout:	Drop-in, 64-3/8" x 27-5/16" (1635 mm x 694 mm)
Minimum flat for door:	0" (0 mm)

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

ADA compliant when installed to the specific requirements of these regulations.