

# KOHLER® Roughing-In

**K-852-H2**  
**TEA-FOR-TWO®**  
**5' BATH WHIRLPOOL**

## Product Information

Applicable product:			
5' bath whirlpool		K-852-H2	
ADA compliant when installed per Section 607 of the Act.			<b>ADA</b>
Fixture*:			
Bathing well:			
Basin area, bottom	40-1/2" (102.9 cm) x 20" (50.8 cm)		
Basin area, top	52-3/4" (134 cm) x 24" (61 cm)		
Weight	290 lbs (131.5 kg)		
To overflow:			
Water depth	13-5/8" (34.6 cm)		
Capacity	60 gal (227.1 L)		
* Approximate measurements for comparison only.			
Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			
Drop-in cut-out	58-1/2" (148.6 cm) x 30-1/2" (77.5 cm)		

Cut-out for undermount	K-586 template
------------------------	----------------

## Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

## Installation Notes

**NOTE:** Pump protrusion beyond rim.

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 60 lbs/square foot (290 kg/square meter) loading.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Fixture conforms to ASME Standard A112.19.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7169-AF or K-7169M-AF)

**K-852-H2**

