

# KOHLER® Roughing-In

K-856-H2, K-856-LH, K-856-RH  
TEA-FOR-TWO®  
5.5' BATH WHIRLPOOL

## Product Information

Applicable products:	
5.5' bath whirlpool – drop-in rim style	K-856-H2
5.5' bath whirlpool with integral flange – left drain	K-856-LH
5.5' bath whirlpool with integral flange – right drain	K-856-RH

Fixture*:	
Bathing well:	
Basin area	45" (114.3 cm) x 25" (63.5 cm)
Top area	58" (147.3 cm) x 29" (73.7 cm)
Weight	510 lbs (231.3 kg)
To overflow:	
Water depth	19-1/2" (27.3 cm)
Capacity (to overflow)	105 gal (397.5 L)
* Approximate measurements for comparison only.	

Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			

## Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control	208-240 V, 20 A, 50/60 Hz
--------------	---------------------------

## Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 86 lbs/square foot (418 kg/square meter) loading.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

A pump/control access panel is required.

For a drop-in installation, the cut-out dimension is 64-1/2" (163.8 cm) x 34-1/2" (87.6 cm).

For an undermount installation, the K-587 template is required.

The hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ASME Standard A112.19.1. All dimensions are nominal.

K-856-H2

No change in measurements if connected with drain illustrated. (K-7147-AF or K-7147M-AF)

