

Product Information

Applicable product:	
Complete bath and shower faucet with K-304-K Rite-Temp valve and slip-fit spout. (shown)	K-12007-4S
Bath and shower trim only with lever handle with NPT spout*	K-T12007-4
Bath and shower trim only with lever handle with slip-fit spout*	K-T12007-4S
Complete shower faucet with K-304-K Rite-Temp valve. (shown)	K-12014-4
Valve trim only with lever handle*	K-T12014-4
Valve trim only with lever handle*	K-T12021-4
*Rite-Temp valve must be ordered to complete faucet.	

Required Accessories:	
Rite-Temp® valve OR	K-304-*
HiFlow Rite-Temp valve with stops	K-2971-KS
* For a complete listing of all the Rite-Temp valves, refer to the K-304-* Specification Sheet or Roughing-In sheet.	

Installation Notes

Install this product according to the installation guide.

NOTICE: Risk of product damage. Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8cm) to 18" (45.7cm) with single elbow between valve and wall-mount spout.

