KOHLER Roughing-In

K-T16233, K-T16234, K-T16235, K-T16246 $\label{eq:margaux} \text{MARGAUX}_{\circledast} \text{ RITE-TEMP}_{\circledast} \\ \text{BATH AND SHOWER TRIM}$

Product Information

Applicable product:	
Bath and shower trim – cross handle	K-T16233-3
Bath and shower trim – lever handle	K-T16233-4
Shower trim only – cross handle	K-T16234-3
Shower trim only – lever handle	K-T16234-4
Valve trim – cross handle	K-T16235-3
Valve trim – lever handle	K-T16235-4
Bath spout	K-16246
Required accessories:	
Rite-Temp _® valve OR	K-304-*
HiFlow Rite-Temp valve with stops OR	K-2971-KS
Rite-Temp valve with diverter OR	K-11748-K
Rite-Temp valve with diverter and stops	K-11748-KS
* For a complete listing of all the Rite-Temp valves, refer to the K-304-* Specification Sheet or Roughing-In Sheet.	
Optional accessories:	
HiFlow Rite-Temp _® thin wall installation kit	88526

Installation Notes

Install this product according to the installation guide. **NOTICE: Risk of product damage.** Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7'' (17.8 cm) to 18'' (45.7 cm) with single elbow between the valve and wall-mount spout.



