

Product Information

Applicable product:	
5' Curved apron bath with Bask heated surface – left drain (shown)	K-1118-LAW
5' Curved apron bath with Bask heated surface – right drain	K-1118-RAW

Fixture*:	
Bathing well:	
Basin area, bottom	45-5/16" (1151 mm) x 25-9/16" (649 mm)
Basin area, top	52-9/16" (1335 mm) x 28-1/16" (713 mm)
Weight	70 lbs (32 kg)
To overflow:	
Water depth	12-11/16" (322 mm)
Capacity	55.6 gal (210.5 L)
*Approximate measurements for comparison only.	

Heater:	W	V	HZ	A
	65	120	60	1.1

Recommended accessories:	
Clearflo cable bath drain with PVC tubing OR	K-7213
Clearflo cable bath drain, less PVC tubing OR	K-7214
Clearflo brass Toe-tap bath drain	K-7259

Installation Notes

Install this product according to the installation guide.

Locate a GFCI-protected 120 V, 15 A, grounded electrical outlet within 24" (610 mm) of the bath junction box.

40" (1016 mm) cable is included.

Floor support under the bath must provide for a minimum of 45 lbs/square foot (219.7 kg/square meter) loading.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

