

### Product Information

Applicable product:				
5.5' Bath whirlpool with integral apron – left drain		K-859-H2		
5.5' Bath whirlpool with integral apron – right drain (shown)		K-860-H2		
Fixture*:				
Bathing well:				
Basin area, bottom	50-3/4" (1289 mm) x 20-5/16" (516 mm)			
Basin area, top	58-7/16" (1484 mm) x 22-5/8" (575 mm)			
Weight	470 lbs (213.2 kg)			
To overflow:				
Water depth	11-11/16" (297 mm)			
Capacity	49 gal (185.7 L)			
*Approximate measurements for comparison only.				
Pump:	kW	V	HZ	A
Variable-speed	1.5	240	50/60	11

Required accessories:	
Jet trim kit	K-9696
Recommended accessories:	
Toe tap bath drain <b>OR</b>	K-7259
Cable bath drain – 30" (762 mm), brass <b>OR</b>	K-37380
Cable bath drain – 30" (762 mm), with PVC tubing	K-37383

### Required Electrical Service

Dedicated circuit required, protected with a Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	208-240 V, 20 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 61.6 lbs/square foot (300.9 kg/square meter) loading.

Will comply with **ADA** when installed per Section 607 Bathtubs of the ADA 2010 Standards for Accessible Design.

Fixture conforms to ASME Standards A112.19.1/CSA B45.2. All dimensions are nominal.

No change in measurement if connected with drain illustrated. (K-7259)

