

Product Information

Applicable product:	
Freestanding bath with fluted apron	K-6369
Fixture*:	
Bathing well:	
Basin area, bottom	24-3/4" (629 mm) x 45-1/4" (1149 mm)
Basin area, top	27-1/4" (692 mm) x 56" (1422 mm)
Weight	117 lbs (53.1 kg)
To overflow:	
Water depth	17" (432 mm)
Capacity	88 gal (333 L)
* Approximate measurements for comparison only.	
Recommended accessories:	
Toe-tap bath drain - with brass tee and pipe	K-7265
PVC cable bath drain - less tee and pipe	K-37385

Required accessories (for K-37385 cable drain only):	
Drain trim - Basic Rotary OR	K-T37391
Drain trim - Contemporary Rotary OR	K-T37392
Drain trim - Traditional Rotary OR	K-T37393
Drain trim - Victorian Rotary OR	K-T37394
Drain trim - Contemporary Push OR	K-T37395
Drain trim - Traditional Push OR	K-T37396
Drain trim - Victorian Push	K-T37397

Installation Notes

Install this product according to the installation guide.



CAUTION: Risk of personal injury. Obtain sufficient help to carefully lift or move the bath.

This bath is designed for freestanding installation only.

Do not support the load weight of the bath by the rim.

Floor support under bath must provide for a minimum of 80 lbs/square foot (390.6 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7265)

