

KOHLER® Roughing-In

K-5244-ET STEWARD® HYBRID HIGH EFFICIENCY URINAL (HEU)

Product Information

Applicable product:	
High Efficiency Urinal (HEU)	K-5244-ET
Fixture:	
Configuration	3/4" top spud urinal
Water per flush	0.125 gpf (0.47 lpf)*
Spud inlet size	3/4"
* Designed to flush with 0.125 gpf (0.47 lpf) of water when installed with a water-saving flushometer.	
Included components:	
3/4" inlet spud	1212716
2" outlet spud	18766
Hanger (2 required)	64512
Universal mounting bracket	1044200
Removable strainer	1195702

Recommended accessories:	
WAVE DC flushometer – 0.125 gpf (0.47 lpf)	K-10668
Touchless DC urinal flushometer with TriPoint™ technology – 0.125 gpf (0.47 lpf)	K-10949
Manual washdown urinal flushometer – 0.125 gpf (0.47 lpf)	K-13520

Installation Notes

Install this product according to the installation guide.

Roughing-in remains the same when using the optional 3" outlet spud.

NOTICE: For ADA compliance, measurement must be from the floor to the top of the internal lip.

Will comply with **ADA** when installed per Section 605 Urinals of the 2010 ADA Standards for Accessible Design.

Fixture conforms to ASME Standard ASME A112.19.2/CSA B45.1. All dimensions are nominal.

