

## Product Information

Applicable product:	
BubbleMassage whirlpool bath with heater - left drain (shown)	K-1124-XHGLA
BubbleMassage whirlpool bath with heater - right drain	K-1124-XHGRA

Fixture*:	
Bathing well	
Basin area, bottom	51-3/8" (1305 mm) x 21" (533 mm)
Basin area, top	64-1/2" (1638 mm) x 30-1/2" (775 mm)
Weight	150 lbs (68 kg)
To overflow	
Water depth	15" (381 mm)
Capacity	72 gal (273 L)
* Approximate measurements for comparison only.	

	V	Hz	A
Motor/pump: 1-speed	120	60	7
Blower:	120	60	10
Heater:	kW		
	1.5	120	60

Pump and blower are supplied with 24" (610 mm) grounding-type plug-in cords.

Required accessories:	
Clearflo slotted overflow brass bath drain <b>OR</b>	K-7271
Clearflo slotted overflow bath drain – PVC pipe	K-7272
<b>Required Electrical Service (3 Required):</b> Three dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/heater/blower	120 V, 15 A, 60 Hz

## Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 44.2 lbs/square foot (215.8 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Will comply with **ADA** when installed per Section 607 Bathtubs of the Act.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7272)

