

5.5' VIBRACOUSTIC® BATH WITH BASK HEATED SURFACE

Product Information

Fixture: Approx.	measurements for comparison only.			
Bathing well:	Bathing well:			
Basin area, bottom	46" (1168 mm) x 30" (762 mm)			
Basin area, top	57" (1448 mm) x 34" (864 mm)			
Weight	96 lbs (43.5 kg)			
To overflow:				
Water depth	16" (406 mm)			
Capacity	95 gal (359.6 L)			

Recommended accessories:		
Pop-up drain – above-the-floor installation	K-7161-AF	
OR Toe-tap drain	K-7265	

Amplifier/ control:	15 W (per channel)	120 V	50/60 Hz	-
Heater:	65 W	120 V	60 Hz	1.1 A

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD): 120 V, 15 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide. Ensure that the interface, amplifier, and transducers are functional before completing the installation.

Control amplifier fits 16" (406 mm) center studs. 25' (7.6 m) cables are included.

Locate the bath within 24" (610 mm) of a GFCI-protected 120 V, 15 A grounded electrical outlet. A second grounded outlet within the wall framing must be within 24" (610 mm) of the planned control amplifier. One electrical service may be used for the entire bath and related electrical components.

Floor support under bath must provide for a minimum of 47.6 lbs/square foot (232.4 kg/square meter).

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.



