

## Product Information

Applicable products:	
6' Bubblemassage bath with Bask	K-1418-GW
Fixture*:	
Basin area:	
Bathing well	48" (1219 mm) x 27" (686 mm)
Top area	60" (1524 mm) x 30" (762 mm)
Weight	156 lbs (70.8 kg)
To overflow:	
Water depth	16" (406 mm)
Capacity	94 gal (355.8 L)
* Approximate measurements for comparison only.	
	V Hz A
Blower motor/Heated surface	220-240 50/60 5
Drop-in cutout	70-1/2" (1791 mm) x 40-1/2" (1029 mm)

## Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Blower motor/Heated surface	220-240 V, 15 A, 50/60 Hz

## Installation Notes

**NOTICE:** Relocation of the blower motor and check valve is optional. Mount the blower motor and check valve together; do not move one without the other. Two access panels are required for blower motor and check valve relocation. Provide one access panel at the blower motor/control location and another at the heated surface location.

Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 54 lbs/square foot (261 kg/square meter) loading.

Locate a GFCI-protected 120 V, 15A, grounded duplex electrical outlet within 24" (610 mm) of the blower motor.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements with drain shown. (K-7161-AF)

