

KOHLER® Roughing-In

K-1947-H, K-1947-LH, K-1947-RH ARCHER® 5' BATH WHIRLPOOL WITH HEATER

Product Information

Applicable product:	
Bath whirlpool – drop-in	K-1947-H
Bath whirlpool – integral flange, left drain	K-1947-LH
Bath whirlpool – integral flange, right drain	K-1947-RH

Fixture*:	
Bathing well	
Basin area, bottom	45-1/8" (1146 mm) x 19-11/16" (500 mm)
Basin area top	52-1/8" (1324 mm) x 22-1/16" (560 mm)
Weight	98 lbs (44.5 kg)
To overflow	
Water depth	15-1/8" (384 mm)
Capacity	57 gal (216.9 L)
* Approximate measurements for comparison only.	
Drop-in cutout	58-1/2" (1486 mm) x 28-1/2" (724 mm)

Pump:	V	Hz	A	
1-speed	120	60	7	
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required accessories:

Clearflo slotted overflow brass bath drain OR	K-7271
Clearflo slotted overflow bath drain – PVC pipe	K-7272

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz

Installation Notes

Install this product according to the installation guide.

Pump is supplied with 24" (610 mm) grounding-type plug-in cord.

Floor support under this product must provide for a minimum of 48 lbs/square foot (234 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Will comply with **ADA** when installed per Section 607 Bathtubs of the Act.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

