

Product Information

Applicable product:	
Cube BubbleMassage bath with Bask – without chromatherapy	K-1969-GW
Cube BubbleMassage bath with Bask – with chromatherapy (shown)	K-1969-GCW

Fixture*:	
Bathing well:	
Basin area, bottom	39-3/8" (1000 mm) x 39-3/8" (1000 mm)
Basin area, top	44-5/8" (1133 mm) x 44-5/8" (1133 mm)
Weight	156 lbs (70.8 kg)
To overflow:	
Water depth	27-1/2" (699 mm)
Capacity	171 gal (647.3 L)
* Approximate measurements for comparison only.	

	V	Hz	A
Blower motor/Heated surface	220-240	50/60	5

Required accessory: Under-mount kit	K-578
-------------------------------------	-------

Recommended accessories: Cable drain	K-8150
Drain trim kit	K-8134

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Blower motor/Heated surface	220-240 V, 15 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

IMPORTANT! This product is intended for under-mount installation only.

Floor support under bath must provide for a minimum of 105 lbs/square foot (513 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-8150)

