KOHLER, Faucets

Artifacts® with Column design

widespread bathroom sink spout **K-72760**

Features

- Metal pop-up drain with tailpiece
- 6-5/8" (168 mm) spout reach
- Includes stationary spout with aerator and pop-up drain with 1¼" tailpiece
- Handles sold separately
- Laminar flow delivers a graceful stream of water
- 1.2 gpm (4.5 lpm) maximum flow rate
- Coordinate with your choice of Artifacts handles for a personalized design



- Brass
- KOHLER finishes resist corrosion and tarnishing

Installation

Widespread

Water Conservation & Rebates

 This product can help a building earn Water Efficiency points in LEED® Green Building Rating System

Required Products/Accessories

K-98068-3 Cross bathroom sink faucet handles

or

K-98068-3M Prong bathroom sink faucet handles

or

K-98068-4 Lever bathroom sink faucet handles

or

K-98068-9M Swing lever bathroom sink faucet handles

Recommended Products/Accessories

K-23726 Drain treatment

K-23723 Faucet cleaner

K-72567 18" Towel Bar

K-72568 24" Towel Bar

K-72570 24" Double Towel Bar

K-72571 Towel Ring

K-72572 Robe Hook

K-72573 Pivoting toilet paper holder

K-72576 Toilet paper carriage





Codes/Standards

ASME A112.18.1/CSA B125.1

NSF/ANSI/CAN 61

NSF/ANSI/CAN 372

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	2BZ	Oil-Rubbed Bronze
	2MB	Vibrant® Brushed Moderne Brass





Artifacts® with Column design

widespread bathroom sink spout K-72760



Technical Information

All product dimensions are nominal.

Faucet:

Flow rate: 1.2 gal/min (4.5 l/min)

Pressure: 60 psi (4.1 bar)

Drain included: Yes
Drain tailpiece Yes

included:

Spout:

Spout reach: 6-5/8" (168 mm)

Notes

Install this product according to the installation guide.

