

# Comfort Height® Touchless Toilet K-6418

#### Features

- Vitreous China
- Elongated Bowl
- Comfort Height<sup>®</sup>
- AquaPiston<sup>®</sup> flushing system
- Touchless Technology allows hands-free operation to actuate the flush
- Less seat and supply
- 1.28 gpf (4.8 lpf)
- 2-1/8" (54 mm) glazed trapway
- 10-1/2" (267 mm) x 7-7/8" (200 mm) water area.

#### Installation

- 12" (305 mm) rough-in
- 28-3/4" (730 mm) x 17-5/8" (448 mm) x 30-3/4" (781 mm)

### **Optional Accessories**

K-4774 Toilet Seat K-4888 Elongated Toilet Seat K-7637 Angle Supply with Stop (single)

#### Components

Product includes: K-4309 Elongated Toilet Bowl K-5692 Toilet Tank Additional included component/s: Bowl, Tank, Tank Cover, and Touchless Flush Kit.





#### **Codes/Standards**

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651 OBC

### KOHLER<sup>®</sup> One-Year Limited Warranty


See website for detailed warranty information.

### **Available Color/Finishes**

Color tiles intended for reference only.

#### Color Code Description

0	White
96	Biscuit
47	Almond
NY	Dune
95	lce™ Grey
G9	Sandbar
7	Black Black™





## USA/Canada: 1-800-4KOHLER (1-800-456-4537) Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to www.kohler.com.

#### Trap passageway: 2-1/8" (54 mm) Water Consumption

**Technical Information** 

Toilet type:

Bowl shape:

3-4-2017 03:52

All product dimensions are nominal.

 Full:
 1.28 gpf (4.8 lpf)

 Water surface size:
 10-1/2" x 7-7/8" (267 mm x 200 mm)

 Rim to water surface:
 6-3/8" (162 mm)

 Rough-in:
 12" (305 mm)

 Seat-mounting holes:
 5-1/2" (140 mm)

Two-piece

Elongated front

#### Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a  $45^{\circ}$  double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing Codes require elongated toilets and elongated, open-front toilet seats in public bathrooms.

Accessibility standards require controls to be located on the open side of the toilet.

## **Cimarron**®

Comfort Height<sup>®</sup> Touchless Toilet **K-6418** 

