

# Kwikset Maximum Security Knob Specifications

## Kwikset Maximum Security Knob Specifications

<b>Door Prep</b>	Crossbore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"
<b>Backset</b>	2-3/8" standard, 2-3/4" optional. UL 2-3/4" standard, 2-3/8" optional.
<b>Door Thickness</b>	1-3/8"-1-3/4" doors standard. 2-1/4" doors optional on 200 and 400 functions only.
<b>Cylinder</b>	5-pin.
<b>Faceplates</b>	1" x 2-1/4" square corner standard. Round corner and other options available.
<b>Strikes</b>	2-1/4" full lip square corner standard. Round corner and other options available.
<b>Bolt</b>	1/2" throw.
<b>Door Handing</b>	Reversible for right- or left-handed doors.
<b>ANSI/BHMA</b>	A156.2 Grade 3.

## Kwikset Maximum Security Knob Dimensions

Dimensions	Design	A	B	C
	Bel Air	2-5/8"	2-3/8"	1-7/8"
	Copa	2-5/8"	2-3/8"	2-1/8"
	Eclipse	2-5/8"	3"	2-1/8"

## Kwikset Maximum Security Knob Finishes

Finish	3	LO3	5	15A	26	260
Bel Air	•	•	•		•	•
Copa	•	•	•	•	•	•
Eclipse	•	•	•		•	•

## Kwikset Maximum Security Knob Function Descriptions

	<b>200</b> <i>F75</i>	<b>Passage/Hall/Closet:</b> Both knobs always free.
	<b>300</b> <i>F75</i>	<b>Privacy/Bed/Bath:</b> Both knobs locked or unlocked by turnbutton inside. Outside knob unlocked by emergency key.
	<b>300</b> <i>F75</i>	<b>Privacy/Bathroom:</b> Same function as 300 above. Inside knob polished chrome.
	<b>400</b> <i>F82</i>	<b>Entry:</b> Both knobs locked or unlocked by key outside or turnbutton inside.
	<b>401</b> <i>F87</i>	<b>Entry:</b> Outside locked or unlocked by key outside or turnbutton inside. Inside always free.
	<b>450</b> <i>F85</i>	<b>Storeroom/Vestibule:</b> Outside unlocked only while key is turned. Inside always free.
	<b>488</b>	<b>Hall Dummy Trim, Surface Mounted:</b> For doors where only a pull is required. No operation.

**Note:** ANSI functions are listed in italics.

# Kwikset Install.

