

## FEATURES & SPECIFICATIONS

### INTENDED USE

Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more.

### CONSTRUCTION

Features a decorative white etched-glass diffuser that provides widespread, uniform illumination. Diffuser twist-locks into housing for a hardware-free appearance and provides easy access for cleaning.

### OPTICS

Produces 1800 lumens at 50,000 hours life.

### ELECTRICAL

Fixture operates at 120 volts, 60 Hz. Standard input = 23 watts, 79 lumens per watt.

Works with most standard incandescent dimmers (see list of approved dimmers).

### INSTALLATION

All mounting hardware included.

### LISTINGS

cUL Certified to US and Canadian standards and listed suitable for damp locations. ENERGY STAR® certified.

### WARRANTY

5-year limited warranty. Complete warranty terms located at

[www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

NOTE: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25°C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

Decorative Indoor



**Doko**  
**LED Glass**  
**Flush Mount**  
HIGH-PERFORMANCE LED



### Specifications

Height: 4.44 (11.3)

Diameter: 16 (40.6)

All dimensions are inches (centimeters) unless otherwise indicated.

### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

**Example: FMDOKL 16 20840**

Series	Module/CRI	Color temperature
<b>FMDOKL 16</b> Doko LED glass flush mount, 16"	<b>208</b> >80CRI	<b>40</b> 4000 K 35 3500 K <sup>1</sup> <b>30</b> 3000 K 27 2700 K <sup>1</sup>

<b>Accessories:</b> Order as separate catalog number.	
DFDOKL 14	16" Doko glass diffuser

### Notes

<sup>1</sup> Minimum 90-day lead time for non-standard color temperatures; minimum 50 order quantity.

# LED Doko Flush Mount

## LIGHTING FACTS

LED

lighting facts®

A Program of the U.S. DOE

Light Output (Lumens)

1550

Watts

23

Lumens per Watt (Efficacy)

67.39

Color Accuracy

85

Color Rendering Index (CRI)

Light Color

Correlated Color Temperature (CCT)

3000 (Bright White)

Warm White

Bright White

Daylight

2700K

3000K

4500K

6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: NJSM-3LPGNE (10/6/2014)

Model Number: FMDOKL 16 20830

Type: Luminaire - Decorative

LED

lighting facts®

A Program of the U.S. DOE

Light Output (Lumens)

1790

Watts

23

Lumens per Watt (Efficacy)

77.83

Color Accuracy

85

Color Rendering Index (CRI)

Light Color

Correlated Color Temperature (CCT)

4000 (Bright White)

Warm White

Bright White

Daylight

2700K

3000K

4500K

6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: NJSM-S3EBAH (10/6/2014)

Model Number: FMDOKL 16 20840

Type: Luminaire - Decorative

### SUGGESTED DIMMERS

The FMDOKL is designed to operate with most standard Triac Based (Forward Phase-Control or Leading Edge) dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.

Manufacturer	Part number(s)
Leviton	6633P
	IPL06
	6674P
	IPE04
	Trimatron 600W
Lutron	DVELV 300P
	Skylark 300P
	NTELV 300
	NLV 600
Synergy	ISD 600 I 120