S Ε Ρ by Lithonia Lighting

# **FEATURES & SPECIFICATIONS**

## **INTENDED USE**

Provides general illumination in residential applications. If required for commercial application or operation more than eight (8) hours per day, consult factory for available options. Ideal for use in foyers, hallways, bedrooms, offices, utility work areas, stairways and many other rooms in the house.

### **ATTRIBUTES**

The beauty of simplicity in low profile styled, round, stay-white, acrylic diffuser, available in four sizes: 11", 14", 19" or 24". These fixtures provide an attractive lowcost lighting solution for every room in the home. Hidden cam-latches provide easy diffuser removal for installation and maintenance.

Fixtures available with lamps and without lamps. Fixtures without lamps are available in either compact double twin tube (DTT) 4-pin or circline T9 fluorescent lamp(s) configurations. Fixtures with lamps include circline T9 4100K fluorescent lamp(s) for energy efficiency, superior color rendering long life.

Standard with electronic ballast (120 volt, 60Hz) ensures no flickering and quiet operation without interfering with other home electronics. For use with nondimmable switches only.

All mounting hardware included.

#### LISTING

CUL listed to US and Canadian safety standards and suitable for damp locations. Fixtures with lamps are ENERGY STAR® certified.

#### WARRANTY

Guaranteed for two years against mechanical defects in manufacture. (excludes lamps)

## DIMENSIONS

Catalog Number


Notes

Гуре


## **Indoor Decorative**

# Low Profile Round Flush Mount

**Circline T9 or Compact DTT Fluorescent** 



Nominal Size	Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Extension* inches (cm)
11" dia		FM22 ACLR LP	(1) 22W circline T9	11" (27.9)	3-1/4" (8.3)
		FMLR22	(1) 22W circline T9	11" (27.9)	3-1/4" (8.3)
		FMLR11 2 13DTT	(2) 13W compact DTT	11" (27.9)	3-1/4" (8.3)
14" dia		FM54 ACLR LP	(1) 22W & (1) 32W circline T9	13-3/4" (34.8)	3-1/2" (8.9)
		FMLR54	(1) 22W & (1) 32W circline T9	13-3/4" (34.8)	3-1/2" (8.9)
	(III)	FMLR14 2 18DTT	(2) 18W compact DTT	13-3/4" (34.8)	3-1/2" (8.9)
19" dia		FM72 ACLR LP	(1) 32W & (1) 40W circline T9	19-1/4" (47)	3-5/8" (9.2)
		FMLR72	(1) 32W & (1) 40W circline T9	19-1/4" (47)	3-5/8" (9.2)
		FMLR19 3 26DTT	(3) 26W DTT	19-1/4" (47)	3-5/8" (9.2)
24" dia.		FMXLR 72	(1) 32W & (1) 40W circline T9	24" (61)	4-3/4" (12)
* Extension from ceiling All dimensions are in inches (centimet					ies (centimeters)



## ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories and replacement parts as separate catalog numbers.

	Options	
11" diameter FM22 ACLR LP FMLR 22	<ol> <li>(1) 22W circline T9 lamp <b>Included</b><sup>2</sup></li> <li>(1) 22W circline T9 lamp <b>Required</b><sup>3</sup></li> </ol>	(Consult factory)
FMLR11 2 13 DTT 14" diameter	(2) 13W compact (DTT) lamp(s) <b>Required</b>	
FM54 ACLR LP FMLR 54	(1) 22W & (1) 32W circline T9 lamp(s) <b>Included</b> <sup>2</sup> (1) 22W & (1) 32W circline T9 lamp <b>Required</b> <sup>3</sup>	
FMLR14 2 18 DTT 19" diameter	(2) 18W compact (DTT) lamp(s) required <b>Required</b> <sup>3</sup>	
FM72 ACLR LP FMLR 72 FMLR19 3 26 DTT	<ul> <li>(1) 32W &amp; (1) 40W circline T9 lamp(s) Included<sup>2</sup></li> <li>(1) 32W &amp; (1) 40W circline T9 lamp Required<sup>3</sup></li> <li>(3) 26W compact (DTT) lamp(s) required Required<sup>3</sup></li> </ul>	
24" diameter FMLXR	(1) 32W & (1) 40W circline T9 lamps <b>included</b> <sup>2</sup>	

Example: FM22 ACLR LP

Notes: Use with non-dimmable switches only.
 *INCLUDES* - circline T9 4100K fluorescent lamp(s)
 Lamp(s) not inluded. Not ENERGY STAR qualified.

## **PHOTOMETRICS**

Full photometric data report available within 2 weeks from request. Consult factory.



An **Scuity**Brands Company

Sheet #: LORF