

| FEATURES & SPECIF | ICATIONS |
|-------------------|----------|
|-------------------|----------|

INTENDED USE

Provides general illumination in residential and commercial applications. Ideal for use as lighting in bathroom/ lavatories, over hospital beds, hallways/corridors stairways and utility areas.

CONSTRUCTION

Contemporary, distinct wing design complements a variety of decors. Curved etched-glass diffuser complemented by polished brush nickel accents and finials. Diffuser provides a uniform illumination. Finials allow easy access for cleaning and maintenance. Available in 2', 3' and 4' lengths.

Includes (2) linear T5, 3000K fluorescent lamps for energy efficiency, superior color rendering and long life. Standard with electronic ballast (120 volt, 60Hz) ensures no flickering and quiet operation without interfering with other home electronics.

For use with non-dimmable switches only.


All mounting hardware included.

LISTING

CUL listed to US and Canadian safety standards and listed suitable for damp locations. ENERGY STAR® qualified. ADA compliant.

WARRANTY

Guaranteed for two years against mechanical defects in manufacture.









Linear T5 Fluorescent





DIMENSIONS

| Nominal Size | Lamp Configuration | Model Number | Number of Lamps | (A) Width inches (cm) | (B) Length inches (cm) | (C) Extension* inches (cm) |
|-----------------|-----------------------|-----------------|--------------------|--------------------------|---------------------------|-------------------------------|
| 2' | | 10842RET5 | (2) 14W linear T5 | 6-9/16" (16.7) | 22-5/8" (57.5) | 3-1/4" (8.3) |
| 3' | | 10843RET5 | (2) 21W linear T5 | 6-9/16" (16.7) | 37-5/8" (94.3) | 3-1/4" (8.3) |
| 4' | | 10844RET5 | (2) 28W linaer T5 | 6-9/16" (16.7) | 48-7/8" (121.9) | 3-1/4" (8.3) |





* Maximum extension from wall

All dimensions are in inches (centimeters).

ORDERINGINFORMATION For sho

For shortest lead times, configure products using **bolded options**.

Example: 10842RET5 BNP

| | | BNP | | | | |
|-----------------------|--|--------|-------------------------|----------------------------------|---|-------------------|
| Series ^{1,2} | | Finish | | Ballast/\ | /oltage ² | Options |
| 10842RET5 | (2′ - (2) 14W linear T5 3000K fluorescent lamps included | BNP | Polished brushed nickel | (blank) | 120-volt residential electronic ballast (standard) | (Consult factory) |
| 10843RET5 | (3′ - (2) 21W linear T5 3000K fluorescent lamps included | | | (Other voltage and ballast types | | |
| 10844RET5 | 4′ - (2) 28W linear T5 3000K fluorescent lamps included | | | consult factory) | | |
| | | | | | | |

Notes

2

- 1 Includes (2) linear T5 3000K fluorescent lamps.
- Use with non-dimmable switches only.

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.



SHEET #: WINV DEC-303