

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination for residential and commercial applications. Ideal for use as lighting in bathroom/lavatories, over hospital beds, hallways/ corridors stairways and utility areas.

A distinctive contoured design complements a variety of decors. Durable milk-white acrylic diffuser provides a widespread uniform illumination. Suitable for vertical or horizontal mounting. Available in 2', 3' and 4' lengths.

Utilizes linear T8 fluorescent lamps for energy efficiency, superior color rendering and long life (not included).

Standard with electronic ballast (120 volt, 60Hz) ensures no flickering and quiet operation without interfering with other electronics. Also available in other ballast configurations.


For use with non-dimmable switches only.

LISTING

CUL listed to US and Canadian safety standard on Residential Electronic (RE) ballast fixtures and suitable for damp locations. ENERGY STAR® qualified. ADA compliant. For Non-RE bllast, UL and CSA (standard) for NOM Certified see options.

WARRANTY

Guaranteed for two years against mechanical defects in manufacture.



Indoor Decorative

Litepuff


Vanity

Linear T8 Fluorescent










DIMENSION

Nominal Size	Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Extension* inches (cm)
2'		11890	(2) 17W linear T8	5" (12.7)	27" (68.6)	4" (10.2)
3'		11891	(2) 25W linear T8	5" (12.7)	39" (99.1)	4" (10.2)
4'		11892	(2) 32W linearT8	5" (12.7)	51" (129.5)	4" (10.2)

^{*} Extension from wall All dimensions are in inches (centimeters)



Example: 11892RE

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories and replacement parts as separate catalog numbers.

Model Number^{1,2} 11890 2' - (2) 17W T8 fluorescent lamps required 11891 3' - (2) 25W T8 fluorescent lamps required 11892 4' - (2) 32W T8 fluorescent lamps required

ORDERING INFORMATION

electronic ballast (standard) (blank) Other voltage and ballast types available (see ballast/voltage)

Residential Ballast³

RE 120 volt residential

Ballast/Voltage4 (blank) RE ballast fixtures only

MVOLT Multi-volt 120 120 volt 277 277 volt

347 volt

Others voltage and ballast types (consult factory) Notes:

Options

GEB Electronic ballast, <20%THD T8 electronic ballast, <10% GEB10IS

THD, instant start **GEB10RS** T8 electronic ballast, 10%

THD, rapid start **NOM** Certified

> (Consult factory for other options)

- Lamps not included.
 Use with non-dimmable switches only.
 Residential electronic ballast standard and requires RE designation.
- 4. No designation for lamp type is required on **RE** ballast fixtures.

Accessories/Replacement parts

DVANPIIFF 24 24" white acrylic diffuser **DVANPUFF 36** 36" white acrylic diffuse **DVANPUFF 48** 48" white acrylic diffuser

Litepuff Vanity

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.



PUFV.pmd