# **BE Series**






#### **Applications**

 These centrifugal, self-priming effluent pumps are designed for installations with septic tanks in areas with drainage problems. Ideal for pumping out flooded basements, livestock watering, flood irrigation and general dewatering.

#### **Features**

- Continuous duty rated, higher than NEMA service factor dual compartment motors equipped with stainless steel shaft and automatic thermal overload protection
  - 1/3 hp (115 V) 9.4 full load amps 1/2 hp (115/230 V) 12.4/6.2 full load amps 3/4 hp (115/230 V) 14.8/7.4 full load amps
- Cast iron casing; 1¼" NPT suction
  & discharge
- Built-in check valve facilitates fast priming and guards against syphoning action
- 4 vane, semi-open gray cast iron impeller with "blind hole" for motor shaft protection
- Carbon/ceramic 5/8" mechanical seal

### **Engineering Data**




| Model  | Suct.<br>NPT | Disch.<br>NPT | Priming<br>Plug NPT | Drain Plug<br>NPT | Slots                            | A                  | В                | С            | D               | Е               | F               | G                | Н              | J               | К               | L               | М            |
|--------|--------------|---------------|---------------------|-------------------|----------------------------------|--------------------|------------------|--------------|-----------------|-----------------|-----------------|------------------|----------------|-----------------|-----------------|-----------------|--------------|
| BE-S33 | 11/4         | 1¼            | 1/2                 | 1/2               | .43" x .93"<br>[10.9mm x 23.6mm] | 4.25"<br>[107.9mm] | 7.25"<br>[184.2] | 10"<br>[254] | 4.9"<br>[124.5] | 6.5"<br>[165.1] | 7.6"<br>[193.1] | 14.4"<br>[365.8] | 3.1"<br>[78.8] | 4.9"<br>[124.5] | 5.5"<br>[139.7] | 6.8"<br>[172.7] | 3"<br>[76.2] |
| BE-S50 | 11⁄4         | 1¼            | 1/2                 | 1/2               | .43" x .93"<br>[10.9mm x 23.6mm] | 4.25"<br>[107.9mm] | 7.25"<br>[184.2] | 10"<br>[254] | 4.9"<br>[124.5] | 6.5"<br>[165.1] | 7.6"<br>[193.1] | 14.4"<br>[365.8] | 3.1"<br>[78.8] | 4.9"<br>[124.5] | 5.5"<br>[139.7] | 6.8"<br>[172.7] | 3"<br>[76.2] |
| BE-S75 | 11/4         | 1¼            | 1/2                 | 1/2               | .43" x .93"<br>[10.9mm x 23.6mm] | 4.25"<br>[107.9mm] | 7.25"<br>[184.2] | 10"<br>[254] | 4.9"<br>[124.5] | 6.5"<br>[165.1] | 7.6"<br>[193.1] | 14.4"<br>[365.8] | 3.1"<br>[78.8] | 4.9"<br>[124.5] | 5.5"<br>[139.7] | 6.8"<br>[172.7] | 3"<br>[76.2] |

<sup>\*</sup>Dimensions measured in inches [mm]

## **Specifications**

| Item No. | Model No. | Listing | НР  | SF   | Volts   |     | Per | forman | ce (gpm | Shut-Off Head | Ship Wt. |     |      |       |
|----------|-----------|---------|-----|------|---------|-----|-----|--------|---------|---------------|----------|-----|------|-------|
|          |           |         |     |      |         | 20' | 25' | 30'    | 35'     | 40'           | 45'      | 50' | (ft) | (lbs) |
| 621805   | BE-S33    | CSA     | 1/3 | 1.95 | 115     | 36  | 30  | 23     | 16      | 9             | -        | -   | 45   | 41    |
| 621815   | BE-S50    | CSA     | 1/2 | 1.90 | 115/230 | 45  | 39  | 31     | 24      | 16            | 8        | -   | 50   | 42    |
| 621825   | BE-S75    | CSA     | 3/4 | 1.65 | 115/230 | 58  | 53  | 44     | 36      | 26            | 18       | 10  | 56   | 43    |

### **Performance Data**





Oklahoma City, OK 73157-2010 Phone: 1.800.701.7894 Fax: 1.800.678.7867 www.LittleGiantPump.com



