



**STANDARD FEATURE(S)**

- Towel bar
- One SS3648 L/R seat
- One SS3648 L/R built-in shelf

**Codes/Standards  
Applicable**

- ANSI Z124.1.2
- CSA B45 Series

Colors

Standard Fiberglass Colors



White 002    Bone (Natural) 004

Non-Standard Fiberglass Colors



Almond 013    Sterling Silver (Gray) 006    Black 015    Ice Gray 017    Sea Foam Green 034    Peach Bisque 043    Fawn Beige 054    Innocent Blush 066

Colors shown are for reference purposes only and are subject to change without notice. Exact matches are not possible with your monitor display or printing method used.

Here are the electrical specifications for all MAAX Professional shower therapeutic systems offered in the United States.

**PLEASE NOTE THAT SOME SYSTEMS MAY NOT BE AVAILABLE ON THE PRODUCT YOU HAVE SELECTED.**

Please refer to the *Common Options* and *Massage System(s)* sections for more details.

**Installation Note**

Install this product according to the *Installation Guide*.

All electrical wiring must be done per national/local electrical codes.

STEAMAX	
Requires a dedicated 240 Volt, 1 phase circuit.	
All acrylic showers	5kW / 240V / 21A
Nuevo™ Shower	6kW / 240V / 25A