

TSEA72™ 1-piece

72" x 36" x 75" | 1822 x 908 x 1905 mm



Codes/Standards Applicable

- ANSI Z124.1.2
- CSA B45 Series

Whirlpool Tub Showers:

- UL1795
- ASME A112.19.7
- CSA C22.2 No. 218.3-93
- CSA B45.10

STANDARD FEATURE(S)

Built-in shelf
Towel bar
Vinyl headrest
Soap dish

PLUMBER FEATURE(S)

Right or left-hand drain, specify when ordering
One-piece installation

Colors

Standard Fiberglass Colors



White 002 Bone (Natural) 004

Non-Standard Fiberglass Colors



Almond 013 Sterling Silver (Gray) 006 Black 015 Ice Gray 017 Sea Foam Green 034 Peach Bisque 043 Fawn Beige 054 Innocent Blush 066

Colors shown are for reference purposes only and are subject to change without notice. Exact matches are not possible with your monitor display or printing method used.

Here are the electrical specifications for all MAAX Professional tub shower therapeutic systems offered in the United States.

PLEASE NOTE THAT SOME SYSTEMS MAY NOT BE AVAILABLE ON THE PRODUCT YOU HAVE SELECTED.

Please refer to the *Common Options* and *Massage System(s)* sections for more details.

| WHIRLPOOL | |
|--|-----------------------------|
| Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option). | |
| Heater: Requires a dedicated circuit protected by a Class GFCI. | |
| Pump | 3/4HP / 120V / 7.5A / 60Hz |
| Heater | 1500W / 120V / 12.5A / 60Hz |

| AEROEFFECT WITH AIR PUSH CONTROL | |
|--|-----------------------------|
| Blower: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option). | |
| Blower | 1.4 HP / 120V / 9.5A / 60Hz |

| COMBINED WHIRLPOOL / AEROEFFECT WITH AIR PUSH CONTROL (W/A) | |
|--|-----------------------------|
| Blower: Requires a dedicated circuit protected by a Class A GFCI. | |
| Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option). | |
| Heater: Requires a dedicated circuit protected by a Class A GFCI. | |
| Blower | 1.4 HP / 120V / 9.5A / 60Hz |
| Pump | 3/4HP / 120V / 7.5A / 60Hz |
| Heater | 1500W / 120V / 12.5A / 60Hz |

| CHROMATHERAPY |
|---|
| Requires a dedicated circuit protected by a Class A GFCI. |

Installation Note

Install this product according to the *Installation Guide*.

All electrical wiring must be done per national/local electrical codes.