
## PRODUCT SPECIFICATIONS 600DVBSC(7) Direct Vent System



## **GLASS VIEWING AREA**

39"W x 20 3/8"H (795 Square Inches)

## TECHNICAL INFORMATION

Max. Btu Input: 26,000 BTU/HR

**Ignition System:** Signature Command™ System

Gas Type: Natural or LP Flue Type: T-Lock Pipe

Termination: Rear/Top Vent Convertible

Clearance to Flue for Interior: 3" Top, 1" Bottom and Sides\*\*

Clearance to Flue for Outside Wall: 1"

Clearance to Fireplace: 1/2" CSA Design Certified

## FIELD INSTALLED ACCESSORIES

Louvers: Polished Brass, Pewter Curved Trim: Brass, Pewter, Black Medium Trim Kit: Brass, Pewter, Black

Variable Thermostat Controlled Forced Air Blower

(160 cfm) - BLOT

Signature Command Forced Air Blower (160 cfm) - BLOTSC

Control Fan and Cord: FK12 FK12 Speed Control: SCVS Tavern Brown firebrick Cottage Red firebrick Mesh Glass Cover

Ambient Technologies  $^{\scriptscriptstyle\mathsf{TM}}$  Remote Controls and Thermostats

Designer Facings

\*\* If vertical rise is 7-1/2 feet or higher when in top vent configuration only, the vent clearance to combustibles is 1" on all sides of the horizontal run.

