PRODUCT SPECIFICATIONS

CDVR36(7) and CDVT36(7) Direct Vent Systems



GLASS VIEWING AREA

29-1/16"W x 20-3/8"H (591 Square Inches)

TECHNICAL INFORMATION

Max. Btu Input: 20,000 BTU/HR

Ignition System: Standing Pilot or Electronic

Gas Type: Natural or LP Flue Type: 4" x 7" Twist-Lock*

Termination: Rear Vent or Top Vent models

Clearance to Flue for Interior: 3" Top, 1" Bottom and Sides**

Clearance to Flue for Outside Wall: 1" Clearance to Fireplace: Zero Clearance

CSA Design Certified

FIELD INSTALLED ACCESSORIES

Louvers: Polished Brass, Pewter Curved Trim: Brass, Pewter, Black Medium Trim Kit: Brass, Pewter, Black

Variable Thermostat Controlled Forced Air Blower 135 cfm) - BLOT

Tavern Brown firebrick (FBCD(R/T)36TB) Natural Gas Conversion Kit (CDV36CKN) LP Gas Conversion Kit (CDV36CKP)

Mesh Glass Cover

Ambient Technologies™ Remote Controls and Thermostats

Wood Cabinet Surrounds

Designer Facings

Current 400DVB trim and facing accessories will fit this unit.

- * Simpson Dura-Vent is approved for Top Vent Applications with (MSPA) Adapter.
- ** If vertical rise is 7-1/2 feet or higher when in top vent configuration only (CDVT), the vent clearance to combustibles is 1" on all sides of the horizontal run.



















