
## PRODUCT SPECIFICATIONS

# D) DESIGNER Direct Vent System





#### **GLASS VIEWING AREA**

Front Opening Width: 32-1/4" Front Opening Height: 19-1/2"

### TECHNICAL INFORMATION

Max. Btu Input: 36,000 BTU/HR

Ignition System: Standing Pilot or Electronic

Gas Type: Natural or LP

Flue Type: Simpson Dura-Vent, Selkirk Metalbestos, MetalFab

Termination: Rear/Top Vent Convertible

Clearance on Flue for Interior: 3" Top 1" Bottom and Sides\*\*

Clearance on Flue for Outside Wall: 1"


Clearance on Fireplace: 1/2" **CSA Design Certified** 


#### FIELD INSTALLED ACCESSORIES

Louvers: Polished Brass, Pewter

Variable Thermostat Controlled Forced Air Blower (160 cfm) - BLOT Ambient Technologies<sup>™</sup> Remote Controls and Thermostats

Wood Cabinets





SIDE VIEW

Gas/Electric



Framing dimensions in illustrations accommodate 1/2" finishing material.













A Brand of Monessen Hearth Systems Co. 149 Cleveland Drive, Paris, Kentucky 40361 www.majesticproducts.com



<sup>\*\*</sup> If vertical rise is 7-1/2 feet or higher when in top vent configuration only, the vent clearance to combustibles is 1" on all sides of the horizontal run.