



Lighting Your Life Since 1970

Product Specifications - 85786WGBO

Job Name:	Job Type:
Quantity:	Comments:



**85786WGBO**  
Oakville EE 1-Light Outdoor Wall Lantern

**Finish**  
Black Oxide

**Glass/Shade**  
Water Glass

**Product Category**  
Outdoor Wall Mount

**Lamping**

Number of Bulbs	1
Light Type	
Bulb Type	GU24
Max Bulb Wattage	26
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,760
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

**Measurements**

Width	12.00"
Height	21.00"
Length	N/A
Extension	15"
Back Plate Width	4.75"
Back Plate Height	8.50"
HCO	10.00"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	16.50 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

**Shipping**

Carton Weight	16.50 lbs
Carton Width	14"
Carton Height	32"
Carton Length	17"
Carton Cubic Feet	4.41
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

**Certification**

Safety Rating	Wet
Energy Star	No
CA Title 24	Yes
CA Title 20	No
ADA	No
Dark Sky	N/A

**Other**

UPC Code	783209107779
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	DIE CAST ALUMINUM

**Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.