

Lighting Your Life Since 1970

Product Specifications - 25051ACP	
Job Name:	Job Type:
Quantity:	Comments



25051ACP

Mini Hi-Bay 1-Light Pendant

Finish Antique Copper Glass/Shade

Product Category

Single Pendant

Lamping	
Number of Bulbs	1
Light Type	
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	N/A

Measurements	
Width	11.00"
Height	16.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	60.75"
Hanging Weight	4.00 lbs
Height Adjustable	Yes
Slope	120°
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	4.00 lbs
Carton Width	13"
Carton Height	12"
Carton Length	13"
Carton Cubic Feet	1.09
Master Pack	0
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

_	-4:5:	4:
	rtifica	
-	<i>i</i> ciiiou	COLL

Othe	r	
Dry UPC	Code	783209111882
No Shad	es Included	N/A
No Cryst	tals Included	N/A
No Diffu s	ser Included	N/A
No Conv	ersion Kit	N/A
N/A Mate	rial	N/A
	Dry UPC No Shad No Cryst No Diffus No Conv	No Shades Included No Crystals Included No Diffuser Included No Conversion Kit

Equivalents	
Incandescent Watts	

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.