

Lighting Your Life Since 1970

Glass/Shade

Other

Dry UPC Code

N/A

No Shades Included

Yes Crystals Included

No Diffuser Included

No Conversion Kit

Material

Product Specifications - 89963WT				
Job Name:	Job Type:			
Quantity:	Comments			

Product Category

Equivalents

Fluorescent Watts

N/A

N/A

783209111653 Incandescent Watts

N/A

N/A

N/A

N/A



Finish

Certification

Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

89963WT

CounterMax MX-L120-EL 13" Under Cabinet

White		Glass/Glade		Under Cabinet	
Lamping		Measurements	4.00	Shipping	4.40 lb -
Number of Bulbs	. = 5	Width	4.00"	Carton Weight	1.10 lbs
Light Type	LED	Height	1.00"	Carton Width	3"
Bulb Type	LED	Length	13.00"	Carton Height	16"
Max Bulb Wattage	6.5	Extension	N/A	Carton Length	6"
Max Fixture Wattage	6.5	Back Plate Width	N/A	Carton Cubic Feet	0.12
Rated Life	±40,000 Hours	Back Plate Height	N/A	Master Pack	10
Rated Lumens	±420	НСО	N/A	Master Pack Weight	17.22 lbs
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack Width	13.50"
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height	11.75"
Light Úp/Down	N/A	Hanging Weight	1.10 lbs	Master Pack Length	16.00"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	1.47
CRI	90+	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A	•	
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Standard/Lutron® or Leviton® CL	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.