

Lighting Your Life Since 1970

Product Specifications - 87807WT						
Job Name:	Job Type:					
Quantity:	Comments					



87807WT

CounterMax MX-FD 24" 1-Light Fluorescent

Finish White		Glass/Shade White		Product Category Under Cabinet	
Wille		· · · · · · · · · · · · · · · · · · ·		Ondor Cabinot	
Lamping		Measurements		Shipping	
Number of Bulbs	1	Width	5.00"	Carton Weight	3.47 lbs
Light Type	Fluorescent	Height	1.25"	Carton Width	6"
Bulb Type	Mini Bi Pin T5	Length	24.00"	Carton Height	2"
Max Bulb Wattage	16	Extension	N/A	Carton Length	25"
Max Fixture Wattage	16	Back Plate Width	N/A	Carton Cubic Feet	0.15
Rated Life	±7,500 Hours	Back Plate Height	N/A	Master Pack	6
Rated Lumens	±1,360	НСО	N/A	Master Pack Weight	25.44 lbs
Color Temp			N/A	Master Pack Width	11.42"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	6.30"
Light Up/Down	N/A	Hanging Weight	3.47 lbs	Master Pack Length	26.38"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	1.10
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	No	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
		.,			
Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209022508	Incandescent Watts	124
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		
-					

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.