



Lighting Your Life Since 1970

Product Specifications - 87809WT

Job Name:	Job Type:
Quantity:	Comments:



**87809WT**  
CounterMax MX-FD 43" 1-Light Fluorescent

**Finish**  
White

**Glass/Shade**  
White

**Product Category**  
Under Cabinet

**Lamping**

Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	Mini Bi Pin T5
Max Bulb Wattage	26
Max Fixture Wattage	26
Rated Life	±7,500 Hours
Rated Lumens	±2,700
Color Temp	±3,100 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	No

**Measurements**

Width	5.00"
Height	1.25"
Length	43.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	4.85 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

**Shipping**

Carton Weight	4.85 lbs
Carton Width	6"
Carton Height	2"
Carton Length	44"
Carton Cubic Feet	0.30
Master Pack	6
Master Pack Weight	33.00 lbs
Master Pack Width	12.38"
Master Pack Height	6.63"
Master Pack Length	44.00"
Master Cubic Feet	2.09
UPS Shippable	Yes

**Certification**

Safety Rating	Dry
Energy Star	No
CA Title 24	Yes
CA Title 20	No
ADA	No
Dark Sky	N/A

**Other**

UPC Code	783209022522
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Steel

**Equivalents**

Incandescent Watts	245
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.