

Lighting Your Life Since 1970

	Product Specifications - 85165GFCO		
Job Name:		Job Type:	
	Quantity:	Comments	



85165GFCO

Balboa VX EE 1-Light Outdoor Wall Mount

ENERGY STAR CERTIFIED

Finish Copper Oxide

Lamning

Lamping	
Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	26
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,760
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

Glass/Shade
Golden Frost

Me	asi	Ire	me	etne

Width	12.00"
Height	17.50"
Length	N/A
Extension	14"
Back Plate Width	6.00"
Back Plate Height	11.50"
HCO	7.00"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	8.38 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Product Category

Outdoor Wall Mount

Shippina

Silippilig	
Carton Weight	8.38 lbs
Carton Width	17'
Carton Height	14'
Carton Length	25'
Carton Cubic Feet	3.50
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification		Other	
Safety Rating	Wet	UPC Code	783209074248
Energy Star	Yes	Shades Included	N/A
CA Title 24	Yes	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Vivex

Equivalents

Incandescent Watts	160
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.