

Lighting Your Life Since 1970

Product Specifications - 85535WTSN				
Job Name:	Job Type:			
Quantity:	Comments			

ė.	1			٨	٥
0	X			×	в
L	V			1	J

85535WTSN

Linear EE 2-Light Vanity

Finish		Glass/Shade		Product Category	
Satin Nickel		White		Bath Vanity	
Lamping		Measurements		Shipping	
Number of Bulbs	2	Width	37.0"	Carton Weight	6.0 lbs
Light Type	Fluorescent	Height	5.0"	Carton Width	7"
Bulb Type	Med Bi Pin T8	Length	N/A	Carton Height	6"
Max Bulb Wattage	25	Extension	4"	Carton Length	39"
Max Fixture Wattage	50	Back Plate Width	2.7"	Carton Cubic Feet	0.92
Rated Life	±10,000 Hours	Back Plate Height	35.2"	Master Pack	4
Rated Lumens	±4,300	НСО	N/A	Master Pack Weight	31.6 lbs
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack Width	39.5"
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height	12.5"
Light Up/Down	N/A	Hanging Weight	6.0 lbs	Master Pack Length	14.4"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	4.11
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	N	Canopy Width			
		Canopy Height			
		Canopy Length	N/A		
		., 0			
Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209093881	Incandescent Watts	436
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	Yes	Conversion Kit	N/A		
Dark Sky	N/A	Material	Metal		
Duin Sky	IN/A	matorial	iviciai		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.