

# Lighting Your Life Since 1970

Product Specifications - 85840MROI			
Job Name:	Job Type:		
Quantity:	Comments		



# 85840MROI

1-Light Flush Mount

Finish	
Oil Rubbed E	ronze

## Lamping

#### **Number of Bulbs** 1 **Light Type** Fluorescent **Bulb Type** GU24 Max Bulb Wattage 13 Max Fixture Wattage 13 **Rated Life** ±10,000 Hours **Rated Lumens** ±900 **Color Temp** ±2,700 K Bulb(s) Included Light Up/Down N/A Beam Spread N/A 81-82 **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable No

## Glass/Shade Marble

# Measurements

Width	11.5"
Height	6.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.3 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

# **Product Category**

Flush Mount

	Shipping	
"	Carton Weight	2.3 lbs
"	Carton Width	12'
١	Carton Height	6'
٨	Carton Length	12'
١	Carton Cubic Feet	0.46
٨	Master Pack	1
١	Master Pack Weight	N/A
٨	Master Pack Width	N/A
١	Master Pack Height	N/A
S	Master Pack Length	N/A
١	Master Cubic Feet	N/A
٨	UPS Shippable	Yes

#### Certification Other

oor timoution		0.1101	
Safety Rating	Dry	UPC Code	783209048683
Energy Star	No	Shades Included	N/A
CA Title 24	Yes	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Steel

## **Equivalents**

Incandescent Watts	82
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.