

Lighting Your Life Since 1970

Product Specifications - 87831SN				
Job Name:	Job Type:			
Quantity:	Comments			



87831SN

CounterMax MX-X120 13" 2-Light 120V Xenon

N/A

N/A

N/A

Finish Satin Nickel

Lamping

Lamping	
Number of Bulbs	2
Light Type	Xenon
Bulb Type	G8
Max Bulb Wattage	20
Max Fixture Wattage	40
Rated Life	±3,500 Hours
Rated Lumens	±450
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shade

Measurements

Width	5.00"
Height	1.25"
Length	13.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	1.90 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A

Product Category

Under Cabinet

	Shipping	
"	Carton Weight	1.90 lbs
"	Carton Width	7'
"	Carton Height	3'
٨	Carton Length	18'
١	Carton Cubic Feet	0.17
٨	Master Pack	6
١	Master Pack Weight	13.20 lbs
١	Master Pack Width	13.90'
١	Master Pack Height	9.40'
3	Master Pack Length	18.10'
١	Master Cubic Feet	1.37
٨	UPS Shippable	Yes

	_			_
Certification		Other	Eaui	valents

Canopy Width

Canopy Height

Canopy Length

ooout.o		0 (1101		=quivaronto	
Safety Rating	Dry	UPC Code	783209107298	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.