



Product Specifications - 1091BK/PHC11

Job Name:	Job Type:
Quantity:	Comments:



**1091BK/PHC11**  
84" Burial Pole with Photo Cell

**Finish**  
Black

**Glass/Shade**

**Product Category**  
Outdoor Accessories

**Lamping**

Number of Bulbs	N/A
Light Type	N/A
Bulb Type	
Max Bulb Wattage	N/A
Max Fixture Wattage	
Rated Life	
Rated Lumens	
Color Temp	
Bulb(s) Included	No
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast	N/A

**Measurements**

Width	3.0"
Height	84.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	7.5 lbs
Height Adjustable	N/A
Slope	N/A

**Shipping**

Carton Weight	7.5 lbs
Carton Width	7"
Carton Height	4"
Carton Length	45"
Carton Cubic Feet	0.73
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

**Certification**

UL/ETL/CSA	N/A
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

**Other**

UPC Code	783209109162
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Aluminum

**Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL, ETL or CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.